## **BMW Motorrad**

## Maintenance schedule

## 0554 - K 1200 RS

00 00 128 BMW Inspection (see Maintenance Schedule) (every 20,000 km)

| Customer                      | Registration No.           | Odometer reading                |                                     |
|-------------------------------|----------------------------|---------------------------------|-------------------------------------|
| Order No.                     | Date                       | Mechanic's + Manager's signate  | ure                                 |
| <br>Reading fault-code mem    | nories with the BMW Mo     | torrad diagnostic system        |                                     |
| Checking freedom of mo        | ovement of throttle cable  | and checking for kinks and ch   | nafing                              |
| Changing engine oil with      | n engine at operating ter  | nperature, replacing oil filter |                                     |
| Changing oil in gearbox,      | , warmed to normal oper    | rating temperature              |                                     |
|                               | ear wheel drive *)         |                                 | every two years or every 40,000 km  |
| <br>Checking front brake flui | id level                   |                                 | _                                   |
| <br>Checking brake-fluid lev  | el, rear brake             |                                 |                                     |
| Checking front brake pa       | ds for wear                |                                 |                                     |
| Checking front brake dis      | scs for wear               |                                 |                                     |
| Checking rear brake pac       | ds for wear                |                                 |                                     |
| Checking rear brake disc      | cs for wear                |                                 |                                     |
| Visual inspection of the I    | brake pipes, brake hose    | s and connections               |                                     |
| Checking clutch fluid lev     | rel                        |                                 |                                     |
| 21 00 505 Change the c        | lutch fluid (during mainte | enance) *)                      | every four years or every 40,000 km |
| 16 12 525 Replace the f       | uel filter (during mainten | nance) *)                       | every 40,000 km                     |
| Checking coolant level a      | and concentration          |                                 |                                     |
| Checking battery acid le      | vel                        |                                 |                                     |
| Cleaning and greasing b       | pattery terminals          |                                 |                                     |
| Replacing intake air filte    | r                          |                                 |                                     |
| Checking operation of si      | ide-stand switch           |                                 |                                     |
| Greasing side stand pivo      | ot                         |                                 |                                     |
| Checking centre stand         |                            |                                 |                                     |



| Checking steering damper  |                 |      |  |  |
|---|-----------------|------|--|--|
| Checking rear wheel bearing play by tilting wheel   |                 |      |  |  |
| Checking swinging-arm pivot mount   |                 |      |  |  |
| Checking valve clearance  |                 |      |  |  |
| 11 31 705 Additional work: Replace liner on chain tensioning rail, slide rail and thrust block (fuel tank / cylinder head cover removed) *) | every 60,000 km |      |  |  |
| Replacing spark plugs   |                 |      |  |  |
| Checking tyre pressures and tread depth   |                 |      |  |  |
| Checking lights and signalling equipment  |                 |      |  |  |
| Test ride as final inspection and function check  |                 |      |  |  |
| Confirming BMW Service in on-board documentation  |                 |      |  |  |
| *) Billed as a separate item  |                 |      |  |  |
| BMW Motorrad, UX-VA-4<br>18.05.06   | BMW recommends  | trol |  |  |